


Gerader Einschraubanschluss

- Whitworth-Rohrgewinde
- gekammerter O-Ring
- Dichtungen FKM
- Werkstoff Ms vernickelt
- Temperaturbereich -20 bis +120 °C
- Arbeitsdruckbereich -0,95 bis 16 bar



Artikel-Nr.	G	für Schlauch	SW1	SW2	i	L1	L2	D1	D2	NW	g/Stück
VT628-0202	G1/8	AD4	13	3	5.5	19.5	10	8.5	14.2	2	9
VT628-0204	G1/8	AD6	13	5	5.5	22	12.5	11.5	14.2	4	10
VT628-0206	G1/8	AD8	14	5	5.5	27	17.5	14.5	15.2	5.1	17
VT628-0404	G1/4	AD6	17	5	7.5	24.5	12.5	11.5	18.5	4	18
VT628-0406	G1/4	AD8	17	6	7.5	27.5	15.5	14.5	18.5	6	21
VT628-0408	G1/4	AD10	17	8	7.5	32.5	20.5	16.5	18.5	8	24
VT628-0409	G1/4	AD12	20	8	7.5	36.5	23.5	20	21.8	8.3	38
VT628-0608	G3/8	AD10	20	8	7.5	30.5	17.5	16.5	21.8	8	32
VT628-0609	G3/8	AD12	20	9	7.5	32.5	19.5	20	21.8	9	35
VT628-0611	G3/8	AD14	22	10	7.5	40	24.5	22	23.8	10.3	51
VT628-0809	G1/2	AD12	24	9	9.5	35	19.5	20	26.2	9	54
VT628-0811	G1/2	AD14	24	10	9.5	36.5	21	22	26.2	10.3	55